


T-CHARGE 26 EVO



- Caricabatterie, mantenitore di carica e tester elettronico multifunzione con schermo LDC per batterie WET, GEL, AGM, MF, PbCa, EFB, Litio a 12V/24V di auto, moto, trattori, furgoni, barche ed escavatori anche a basse temperature. Completo di cavo con pinze e cavo con occhielli (alimentatore accendisigari 12V opzionale cod. 804038).
- INTELLIGENTE: la tecnologia avanzata Pulse Tronic (made in Telwin) è studiata per aumentare l'efficienza e la durata nel tempo della batteria. Gli 8 step di carica si basano su una diagnosi puntuale, istante per istante, delle condizioni della batteria.
- Funzione BOOST per ricarica rapida; funzione TEST alternatore, avviamento e stato di carica della batteria; funzione SUPPLY per l'alimentazione continua durante i cambi batteria e non perdere le memorie del veicolo; funzione RECOVERY per rigenerare le batterie solfatate allungandone la vita tramite un processo ad impulsi.
- SICURO: le numerose protezioni (sovraccarico, cortocircuito, inversione di polarità) garantiscono massima sicurezza all'operatore e integrità alla batteria.
- FACILE E COMPATTO: collega T-Charge alla batteria e scegli la funzionalità da usare, al resto pensa lui. Visualizzazione immediata del livello di carica. Grazie alle dimensioni e al peso ridotti, T-Charge può essere trasportato e posizionato dovunque, anche dove lo spazio è limitato.

DESCRIPTION

Multi-functional electronic battery charger, trickle charger and tester for WET, GEL, AGM, MF, PbCa, EFB, Li 12V/24V batteries with LCD display.

Charging and maintenance programs in Pulse Tronic dedicated to the technology of the selected battery. BOOST function for quick charge. Advanced function for charging and maintenance of batteries at low temperatures. Activation of the RECOVERY function enables resetting of sulphated batteries. Tests the vehicle alternator and battery. Continuous and reliable power supply source during battery changes. Simplified use and immediate display of the parameters thanks to the LCD display.




Features:

- Automatic charge and maintenance in Pulse Tronic based on the technology of the selected battery;
- BOOST function for quick charge of the batteries;
- COLD function to charge and maintain batteries at low temperatures;
- RECOVERY function to recover sulphated batteries;
- TEST function for battery, starting and alternator;
- SUPPLY function for stable power supply during battery changing;
- LCD display;
- Protection against overcharge, short circuit and polarity reversal.

Complete with cable with clamps and cable with eyelets.



TECHNICAL DATA

CODE	CODE 807595	V_{1PH}	SINGLEPHASE MAINS VOLTAGE 230 V	F	MAINS FREQUENCY 50 / 60 Hz
P	CHARGING ABSORBED POWER 232 W		CHARGING VOLTAGE 12 / 24 V	A_{EFF}	EFFECTIVE CHARGING CURRENT 16 / 8 A
A_{EN}	RATED CHAR.CUR.EN60335-2-29 16 / 8 A		MIN.RATED REFERENCE CAPAC. 10 Ah		MAX.RATED REFERENCE CAPAC. 250 Ah



PROTECTION DEGREE
IP44



DIMENSIONS (LxWxH)
27 x 12 x 6,7 cm



WEIGHT
1,6 kg

ON REQUEST ACCESSORIES

MAGNETS 2 PCS
803088

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



BROCHURE